

Breast Milk Refrigerator S Series

The Pinnacle purpose built breast milk storage refrigerators and freezers have been designed in Australia specifically for the storage of expressed breast milk. Ideal for hospitals and birthing suites, they provide reliable temperature control and are easy to use.

Features:

- ✓ **+2°C to +4°C Operating Temperature Range**
With exclusive Blue Bottle product temperature simulation ²
- ✓ **Digital Controller** ¹
With battery backup providing 24 hours of temperature readings during power outage
- ✓ **Alarm System**
Alarms when door open and/or out of temperature range
- ✓ **Min / Max Temperature Logging**
- ✓ **Building Management System (BMS) Connection**
- ✓ **Fan Forced Cooling**
- ✓ **Internal Fan Switch**
Will turn off fan when door open
- ✓ **Energy Efficient and Quiet**
Double glazed Low-E glass doors and superior insulation
- ✓ **LED Lighting**
- ✓ **Door Lock** ³
- ✓ **Cable Port**
- ✓ **Cyclic Defrost**
- ✓ **Warranty**
1 year labour and 2 years parts



Product code: PBMR-S-36-1-GD

Optional Features:

- Low Temperature Cut-out
- 4G SMS Auto-dialler
- Additional Wire Coated Shelving
- Guardian T Alarm Testing System
- 7 Day Chart Recorder



1



2



3

Breast Milk Storage S Series



Technical Specifications

Model	REFRIGERATOR PBMR-S-36-1-GD	REFRIGERATOR PBMR-S-145-1-GD	FREEZER PLUF-S-20-115-1-SD		
Storage Capacity (litres)	36L	145L	115L		
Voltage	220 VAC - 240 VAC 50Hz				
Amperage	0.8 Amps	1.05 Amps	1.05 Amps		
Size External (W x D x H)	450mm x 470mm x 535mm	610mm x 610mm x 820mm	610mm x 610mm x 820mm		
Weight	27kg	43kg	41kg		
Refrigerant	R134a				
Warranty Labour (refer to full warranty conditions)	1 Year				
Warranty Parts (refer to full warranty conditions)	2 Years				
Number of Shelves	2 + Base	3.5 + Base	3.5 + Base		
Alarm Points	+1°C to +5°C		-10°C to -30°C		
Digital Controller with LCD Display	Included				
Battery Back Up on Controller					
Min / Max Temperature Logging					
Door Open Alarm					
High Temperature Alarm					
Low Temperature Alarm					
Power Loss Alarm				BMS Only	
Remote Alarm Contacts (BMS)	Included		Included		
Internal Fan Switch			N/A		
Cable Port Hole			Included		
Fan Forced Cooling			Static cooling		
Door Lock and Keys			Included		
High Efficiency Insulation			Included		
Glass Door with Double Layer Low-E Glass			Solid door only		
Self Closing Doors			Included		
LED Lighting			No		
Defrost			Cyclic	Cyclic	Manual
Guardian T Alarm Testing Facility			Optional		Optional
External Temperature Logger					Optional
7 Day Chart Recorder					Optional
Low Temperature Cut Out	N/A				
Auto Dialler	Optional				
Additional Shelving	N/A				
Customised Shelving	Optional				
Solid Door	Optional	Solid Door Only	Solid Door Only		
External Construction	Colorbond® Steel				
Door Hinge Right-hand Open	Standard				
Door Hinge Left-hand Open	Optional				
Adjustable Feet	Included				
Power Cord Length	2.5m				

Authorised Sales Agent



P: 1300 358 045
 F: (07) 3376 5433
 E: sales@cskgroup.com.au
 W: cskgroup.com.au